



AVVOLGIMENTO - WINDING - ENROULEMENT - WICKLUNG

	DP	A	FUNI ROPES CABLES SEILE	GOLE GROOVES GORGES RILLEN	m	B	L
Standard	215	240	6	1	19	237	457
Speciale Spécial Special Spezielle	215	246	6	2	7,6		
	270	220	7	1	18,5	227	437
				2	8		

M50T

**FORZA DI TIRO - TRACTION FORCE - FORCE DE TRACTION - ZUGKRAEFTE
ARGANO - GEARBOX - TREUIL - GETRIEBE: M50T**

TAMBURO DRUM TAMBOUR TROMMEL	RAPPORTO RATIO RAPPORT ÜBERSETZUNG	MOTORE - MOTOR - MOTEUR - MOTOR			
		RPM. 1500		RPM. 1000	
		VELOCITÀ SPEED VITESSE GESCHWINGKEIT SYNC.	1.5 (H.P.) 1.1 (KW.)	VELOCITÀ SPEED VITESSE GESCHWINGKEIT SYNC.	1 (H.P.) 0.7 (KW.)
mm	mm	m/sec.	kg.	m/sec.	kg.
215	1/53	0,32	146	0,21	139
270	1/53	0,4	117	0,27	110
215	1/41	0,41	119	0,27	111
270	1/41	0,52	95	0,34	89

SOLO PER MONTACARICHI - ONLY SERVICE LIFT - SEULEMENT POUR MONTE CHARGE - NÜR FÜR KLEINGÜTERAUFZUG. (EN81-3)

CARICO STATICO - STATIC LOAD - CHARGE STATIQUE - STATISCHE BELASTUNG

kg. 650 max

CAPACITÀ OLIO - OIL CAPACITY - CAPACITE HUILE - OELMENGE:

L, 1

PESO ARGANO - GEAR WEIGHT - POIDS TREUIL - GETRIEBEGEWICHT:

kg. 50

